



Public Works Department

HIGHWAY CONSTRUCTION AND ENGINEERING DIVISION

1 N. University Drive, Box B300, Plantation, Florida 33324-2038 • 954-577-4555 • FAX 954-357-5715

M E M O R A N D U M

DATE: July 1, 2022

TO: Josie Sesodia, Director
Urban Planning Division

FROM: David (D.G.) McGuire, Construction Project Manager
Plat Section, Highway Construction and Engineering Division

Noemi Hew, Planner
Transportation Department, Service Development

SUBJECT: Application for New Plat - Letter to Proceed
U-Haul North Pompano (030-MP-21)

The Highway Construction and Engineering Division, Traffic Engineering, and the Transportation Department, Transit Division have reviewed the application for a new plat. Our review included the information contained in the application, the property survey, the site plan (or conceptual access plan), and any previously recorded plats.

As a result of our review, staff has determined that the comments and recommendations are required with respect to the safe and adequate access standards of the Broward County Land Development Code.

STAFF RECOMMENDATIONS

NON-VEHICULAR ACCESS LINE REQUIREMENTS

It is the express intent of this non-vehicular access line to eliminate all proposed openings and existing driveways not specifically delineated in the following comments:

- 1 Along the ultimate right-of-way for NE 48th Street except at the following:
 - A) 30-foot opening with centerline located approximately 66 feet east of the west plat limits. This opening is restricted to and physically channelized for right turns IN only.
 - B) 30-foot opening with centerline located approximately 116 feet east of the west plat limits. This opening is restricted to and physically channelized for right turns OUT only.

ACCESS REQUIREMENTS

- 2 The minimum distance from the non-vehicular access line of NE 48th Street, at any ingress or egress driveway, to the outer edge of any interior service drive or parking space with direct access to such driveway shall be 50 feet.
- 3 A channelized driveways shall consist of one lane each with a pavement width of 16 feet and a minimum inside radius of 40 feet.

TRAFFICWAYS IMPROVEMENTS (Secure and Construct)

- 4 The physical channelization of the driveway in each 30-foot opening on NE 48th Street as specified under the non-vehicular access line requirements.
- 5 The removal of all existing driveways in locations not consistent with approved openings in the non-vehicular access line and the construction of curb, gutter, and sidewalk in these openings when necessary to complete the required improvement.

SIDEWALK REQUIREMENTS (Secure and Construct)

- 6 Along NE 48th Street adjacent to this plat.

COMMUNICATION CONDUIT/INTERCONNECT (Secure and Construct)

- 7 The developer shall be responsible for replacement of communication conduit/interconnect that is damaged by construction of the required improvements. The security amount for communication conduit/interconnect along NE 48th Street shall be determined by the Traffic Engineering Division.

PAVEMENT MARKINGS AND SIGNS (Secure and Construct)

- 8 Construction of the required improvements shall include installation of signs and thermoplastic pavement markings. Pavement markings and signs shall be designed, fabricated, and installed in accordance with Traffic Engineering Division standards. The minimum-security amount for pavement markings and signs is \$1,000.

IMPROVEMENT AGREEMENT AND SECURITY REQUIREMENTS

- 9 Section 5-184(d)(2) of the Broward County Land Development Code requires a recordable agreement for the required improvements. The owner of this plat shall enter into the standard Installation of Required Improvements Agreement (CAF#450) and submit it to the Highway Construction and Engineering Division for review and approval prior to plat recordation. The completion date for all required improvements listed as Exhibit "B" shall indicate completion prior to issuance of Certificates of Occupancy. Alternate phasing schedules must receive prior approval from the Highway Construction & Engineering Division. The use of a non-standard agreement will require independent approval by the County Commission.

The Installation of Required Improvements Agreement shall be secured by letter of credit, cash, lien, or other security acceptable to the County. Security instruments for all required improvements shall be submitted prior to NVAL Amendment Agreement recordation and/or commencement of construction. Security amounts shall be based upon the one of the following:

- a. Approved construction plans. When security is based on approved construction plans, the security will be calculated at one hundred (100%) percent of the cost of the improvements. Requirements for submitting construction plans are outlined below.
- b. Engineer's cost estimate. When security is based on an engineer's cost estimate, the security will be calculated at one hundred twenty-five (125%) percent of the cost of the improvements. Engineer's cost estimate(s) must be submitted for review by the Highway Construction and Engineering Division. Use of approved cost estimate forms is required. Payment of the applicable review fee is required pursuant to Chapter 38.8 of the Broward County Administrative Code.
- c. All forms are available on the Highway Construction & Engineering Division's web page at:
<http://www.broward.org/Publicworks/BCEngineering/Pages/Default.aspx>

IMPROVEMENT PLAN SUBMITTAL (Pre-construction and Security Release Requirements)

- 10 Construction plans for the required improvements (including pavement marking and signing plans) shall be submitted to Highway Construction and Engineering Division for review and must be approved prior to the commencement of construction. Construction shall be subject to inspection and approval by the County. Pavement marking and signing shall be provided for all of the Improvements and shall be subject to review, field inspections and final approval by the Traffic Engineering Division. Security for pavement markings and signing shall not be released without field inspection and final approval by the Traffic Engineering Division of all materials, installations and locations.
- 11 Communication Conduit/Interconnect plans (3 sets and a cost estimate) shall be submitted to the Traffic Engineering Division. Any easements necessary for relocation and maintenance of the conduit must be provided and shown on the submitted plans. No security shall be released without field inspection and final approval of all materials, installations and locations by the Traffic Engineering Division.

GENERAL RECOMMENDATIONS

- 12 Distance and measurement recommendations contained in this report were based on the best information available at the time of review. County staff may approve minor adjustments based on verified field conditions or details provided in approved construction plans.
- 13 All construction must include all necessary transitions to existing pavement, the lengths of which shall be determined by the design speed of the roadway. All designs, construction, studies, etc., shall conform to the applicable sections of the following:
 - A) United States Department of Transportation: "Manual on Uniform Traffic Control Devices" (MUTCD).
 - 1) State of Florida Department of Transportation:
 - 2) "Roadway and Traffic Design Standards."
 - 3) "Standard Specifications."
 - 4) "FDOT Transit Facilities Guidelines."
 - B) Broward County: "Minimum Construction Standards for Roadways Under Broward County Jurisdiction" (Exhibit 25A of Section 25.1, Broward County Administrative Code).

In addition, all designs for construction shall be certified by a Professional Engineer, registered in the State of Florida, that they meet the standards included above.

All standard forms are available for downloading from the Highway Construction and Engineering Division's website:

<http://www.broward.org/Publicworks/BCEngineering/Pages/Default.aspx>.

- 14 This plat will not be recorded until all real estate taxes (including taxes for the current year and any delinquent taxes) for the property being platted have been paid as required by Florida Statutes Chapter 197.192. The applicant shall request a current tax letter be forwarded from the Revenue Collection Division to HCED Plat Section.

F.S. 177 PLAT REVIEW COMMENTS

The following comments note the corrections necessary for the plat mylar to comply with the requirements of Florida Statutes Chapter 177. If additional clarification is necessary, please contact Jason Espinosa at (954) 577-4593 or via email at JESPINOSA@BROWARD.ORG.

Please note that additional changes made to the plat mylar beyond this list of corrections may necessitate additional review time; delay recordation; and result in additional review fees.

All resubmittals shall include a paper copy of the plat with changes from the original plat review application highlighted.

15 SURVEY DATA

- A. The legal description in the title opinion or certificate shall match the legal description on the plat. The plat drawing shall follow the legal description. Explain the calls in the description to monuments that do not appear on the plat. The monuments appear not to be calls in the vesting deed for the parcel to be platted. If the monuments were found on the survey and replaced with P.R.M.s, note such on the survey. If applicable, remove the calls to the monuments from the description. Review and revise as necessary.
- B. Show any found monumentation at the Point of Commencement.
- C. Bearings and distances shall be on all lines.
- D. Plat boundary perimeter closure shall be within +/- 0.03 feet
- E. Land corner coordinates shall be verified with resurvey.
- F. P.R.M. coordinates shall be accurate within +/- .05 feet. (Resurvey sections).
- G. Square footage shall be shown for each parcel. The total area shall be accurate to the nearest square foot.
- H. Bearings, angles, and dimensioning shall be shown for each lot or parcel. Curvilinear lot lines shall show the radii, arc distances, and central angles. Radial lines will be so designated.

- I. Full dimensioning and square footage shall be shown on all right-of-way dedicated by this plat.
- J. P.R.M.s shall be shown at every change of direction, not more than 1,400 feet apart P.R.M.s shall be labeled "Found" or "Set".
- K. Show P.C.P.s as appropriate.
- L. Two land ties to two independent land corners or one land corner and one other recorded corner shall be shown. Show found monumentation at both corners. Identify the location of the found monument 510.03' east of the southeast corner of this plat.
- M. Identify a well-established and monumented Basis of Bearings reference line. Depict the line with its monumentation and ties to the plat boundary. Describe the line in the Plat Notes.
- N. Fully describe NGS Control Point "N 548", including its location and type of monument.
- O. Define the adjustment (e.g., 1990, 2011) of the NAD 83 bearings and coordinates shown on the plat.
- P. Revise Plat Note #1 to indicate that the **BOUNDARY** information was established by the referenced survey firm.
- Q. Show bearing – distance dimensions from the intersection of the northerly extension of the east plat boundary with the north line of the underlying Tract 1 to the apparent westernmost northwest corner of PARCEL "A" per P.B. 183, PG. 234, B.C.R. Show a label for that corner.
- R. Show a distance dimension from the above-mentioned plat corner to the northwest corner of this plat.
- S. Explain the depiction of the 95.05' distance dimension on the north line of this plat. If applicable, remove the dimension and associated leader arrow.
- T. Explain or remove the leader arrow on the north line of Tract 1 north of the west end of the above mentioned 95.05' distance dimension.
- U. Explain or remove the 203.30' distance dimension on the west line of this plat.
- V. Identify or remove the leader arrows at the south end of the west line of this plat.
- W. Explain the depiction of the 139.32' distance dimension at the west end of the south line of this plat. If applicable, remove the dimension and associated leader arrows.
- X. Tie the benchmark shown to the plat boundary.
- Y. All interior excepted parcels shall be clearly indicated and labeled as: "NOT A PART OF THIS PLAT."
- Z. The platting surveyor shall submit Certified Corner Records for section corners used in preparation of the plat to both the State and Broward County. County staff will confirm submittal to the State prior to plat recordation. For section corners which have Certified Corner Records on file, the surveyor shall submit an affidavit confirming that the Section corner was found to be substantially as described in the most recently available certified corner record. Standard affidavit forms are available at:
<http://www.broward.org/BCEngineering/Pages/PlatSectionForms.aspx>.

- AA. The surveyor shall submit digital plat information (after all corrections are completed and Highway Construction & Engineering Division staff requests digital information).

16 RIGHT OF WAY DELINEATION AND DEDICATION LANGUAGE

- A. Dedication language shall clearly dedicate all right-of-way, specific purpose parcels and easements shown on the plat.
1. Remove the reference to PARCEL "A" in the Dedication.
 2. Explain the inclusion of the Section, Township and Range in the Dedication. That information is typically not shown on Broward County plats. Additionally, the Section number in the Dedication does not match the description. Review and revise as necessary.
 3. The name of the plat as shown in the Dedication differs from the name on the plat title. Review and revise as necessary.
 4. Explain the reference to PARCELS "B" and "D" in the Dedication. Those parcels do not appear on the plat drawing. Review and revise as necessary.
- B. Mortgagee dedication shall clearly join in the dedications on the plat, if applicable.
- C. Proposed right-of-way shall be clearly labeled and dedicated by the plat.
- D. Depict the entire right-of-way width of N.E. 48th Street adjacent to the plat. Label the right-of-way shown with all recorded instruments which establish public rights-of-way adjacent to this plat.
- E. Centerlines of right-of-way and construction (if they are different) shall be shown.
- F. All proposed easements shall be clearly labeled and dimensioned. Utility easements should be granted to the public (or to the City– but not to any specific utility company). Utility easements created by the plat should NOT be located within any road right-of-way.
- G. All existing easements shall be clearly labeled and dimensioned. Refer to the Opinion of Title and Adjacent Right-of-Way Report.

17 TITLE CERTIFICATION AND DEDICATION SIGNATURE BLOCKS

- A. Plat review service charge form, review fee, and one copy of the plat with all changes from the original plat review application highlighted. The original plat mylar shall be submitted to the Highway Construction and Engineering Division accompanied by an original title certificate or an attorney's opinion of title which shall:
- 1) be based upon a legal description that matches the plat.
 - 2) be based upon a search of the public records within forty-five (45) days of submittal.
 - 3) contain the names of all owners of record.

- 4) contain the names of all mortgage holders of record and if there are no mortgages, it shall so state.
- 5) contain a listing of all easements and rights-of-ways of record lying within the plat boundaries.
- 6) contain a listing of all easements and rights-of-ways which abut the plat boundaries and are necessary for legal access to the plat, and if there are none it shall so state.

NOTE: The name of the owner as shown on the plat differs from the owner listed in the Opinion of Title. Review and revise as necessary.

The title shall be updated for review of any agreements and the recordation process. Standard format for Title Certificates, Opinions of Title, the Adjacent Right-of-way Report, and a Guide to Search Limits of Easements and Right-of-way may be obtained by contacting the Highway Construction & Engineering Division or by visiting our web site: <http://www.broward.org/BCEngineering/Pages/PlatSectionForms.aspx>

- B. The Dedication on the original mylar shall be executed by all record owners with original signatures. For property owned by an individual (or by individuals), the plat shall be executed in the presence of two witnesses for each signature. Property owned by corporations shall be executed by at least one of the following officers: the President, Vice President, or Chief Executive Officer together with either (i) two witnesses or (ii) the Corporate Seal. A plat which has been executed by any officer other than the President, Vice President, or Chief Executive Officer shall also provide documentation authorizing the individual(s) who executed the plat. The officers executing a plat shall be verified through the Florida Department of State, or by the applicant providing corporate documentation. Persons executing plats owned by a partnership or a trust shall provide documentation clearly demonstrating their authority to execute on behalf of the partnership or trust.
- C. All mortgagees shall execute the plat with original signatures, seals, and witnesses.
- D. Acknowledgments and seals are required for each signature.
- E. Reverse the order of the owner dedication and acknowledgement signature blocks.

18 DRAFTING AND MISCELLANEOUS DATA

- A. Address any undefined abbreviations or symbols used on the plat or added during revision. Remove any abbreviations and symbols from the Legend that do not appear on the plat. Add any missing abbreviations and symbols to the Legend that appear on the plat or are added during revisions.
- B. Notes and/or Legend shall be shown on ALL drawing pages.

- C. The “NOTICE” requirement re: graphic vs. digital format and “additional restrictions that are not recorded on this plat” per 177.091(27) shall be included.
- D. The Utility Easement Note per FS 177.091(28) shall be included.
- E. Plat borders shall be 1/2-inch on three sides with a 3-inch margin on the left side.
- F. Location Map and Scale (Depicting 2 major street names; one North/South and one East/West) shall be shown.
Remove one of the two north arrows on the Location Map.
- G. Scale and Scale Bar shall be shown on each drawing sheet with standard engineering scale of 1" = 20', 30', 40', 50', 60', and 100' or as approved by the Engineering Division.
Remove one of the two graphic scale bars on the plat drawing sheet. Label the beginning and end points of the scale bar.
- H. The plat shall be prepared by a professional surveyor and mapper with the name of the professional surveyor and mapper or legal entity, along with the street and mailing address, shall be shown on each sheet included.
- I. The sheet page numbers, and total of pages shall be shown on each page.
- J. Title block shall include the name of Plat, Subtitle/Replat, Section-Township-Range, City, County, and State.
 - 1. In the plat subtitle, indicate that this plat is a REPLAT of a portion of the underlying Tract 1.
 - 2. Show the City, County and State in which the plat lies in the plat subtitle.
- K. The plat original shall be drawn with black permanent drawing ink; or nonadhered scaled print on a stable base film.
- L. The sheet size shall be 24 inches by 36 inches.
- M. North Arrow(s) shall be shown on each drawing page.
- N. Adjacent plats shall be identified or unplatted parcels shall be identified as “Acreage.”
Remove the folio numbers and ownership information from the labels for this plat and the abutting parcels. Show a label for a portion of the Tract per the underlying plat in the easterly abutting parcel.
- O. Lot, Block, Tract, or Parcel #s or letters shall be shown.
Identify the parcel created by this plat on the plat drawing.
- P. Space for Plat Book and Page shall be shown inside the border in the upper right-hand corner on each page.
- Q. Plat limits shall be labeled and shown with a heavy line.
- R. Match Lines shall be shown for multi-page plats.
- S. The Planning and Development Management Division file number 030-MP-21 shall be shown inside the border in the lower right-hand corner on each page.
- T. Tabular data shall be verified.
- U. Lettering on the plat shall be no smaller than 0.10" (10-point font).
- V. No text on the plat drawing should be obstructed or overlapped by lines or other text.
- W. Remove the depiction of the railroad tracts in the Florida East Coast Railroad right-of-way.

- X. Identify or remove the solid lines on both sides of and adjacent to the centerline of the 100-foot-wide railroad right-of-way.

19 SIGNATURE BLOCKS

- A. The Surveyor's Certification shall be signed, and the plat sealed by professional surveyor and mapper, and state that the plat was prepared under his or her direction and supervision, and complies with all of the survey requirements of FS Chapter 177. The printed name and registration number of the professional surveyor and mapper shall appear directly below the Surveyor's Certificate, along with the printed name, address, and certificate of authorization number of the legal entity.
 - 1. Show the Certification of Authorization number of the entity preparing the plat beneath the address.
 - 2. Remove Part 1 from the references to F.S. 177 in both signature blocks where it appears.
- B. The plat shall include space for signature by the **Highway Construction and Engineering Division** Director and Surveyor indicating that the plat has been reviewed for conformity with Chapter 177, Florida Statutes. Add the letters **LS** to the registration number of the H.C.E.D. reviewing surveyor.
- C. The plat shall include space for signature by the **Broward County Environmental Protection and Growth Management Department**.
- D. The plat shall include space for signature by Records Division - Minutes Section (County Commission).
 - 1. The text in the referenced signature block is incorrect. Refer to the plat recorded in P.B. 183, PG. 496, B.C.R. and revise as necessary.
- E. The plat shall include space for signature by Planning Council Chair and Executive Director.
- F. If applicable, the plat shall include space for approval of Drainage District, City, special improvement district, or taxing district (including space for seals). The language preceding the designated municipal official's signature on the plat drawing shall include the following wording:

"Concurrency/impact fees for the construction, expansion, and/or conversion of a building within this plat shall be paid on the date of building permit issuance"

Revise the text in the City of Pompano Beach signature block, as necessary.
- G. The plat shall include proper dates for signatures.

- H. The original plat mylar shall be submitted to the Highway Construction and Engineering Division accompanied by a copy of the City of Pompano Beach conditions of approval. (Agenda Report or Resolution listing all of the conditions of municipal plat approval.)

20 HIGHWAY CONSTRUCTION & ENGINEERING DIVISION INTERNAL PROCEDURES
(These items are required for plat recordation but are completed by County staff)

- A. Planning Council Executive Director or Designee Signature
- B. Completion of all POSSE Inputs; Impact Fee and Security reports printed
- C. County Surveyor Signature
- D. PRM's Verified
- E. Development Order, Planning & Development Management Division Director Signature
- F. Highway Construction and Engineering Director Signature
- G. City/District scanned copy of mylar, as required.